

ALGERASE

TECHNICAL DATA



ALGERASE

A water-soluble cleaner for use on all outdoor areas such as stairs, paths, terraces, walls, grave stones, etc and is ideally suited for preventative treatment against green, slippery deposits.

Removes:

- Green algae

Prevents:

- Algae growth including black spot

DESCRIPTION

EarthWorks Algerase™ is a highly effective, concentrated product designed to remove green algae, slime, moss and other plant derived deposits. Algerase™ is self-acting and requires no scrubbing, is easy to use and also prevents re-growth of green algae and “black spot” for up to one year. It does not contain acid or chlorine.

Not suitable for removing “black spot” algae – use Biorase for this.

USES

Use on natural stone, concrete flagstones, cement, bricks and wooden surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface color stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

1. Always test first
2. Read entire label and product technical bulletin before using;
3. Wear appropriate skin and eye protection
4. Use when surface temperature is between 50°F and 77°F (do not use on warm surfaces)
5. Shield treated surfaces from rain for approximately 4 hours.
6. Product is very toxic to aquatic life. Do not allow to contaminate ponds, streams or rivers

INSTRUCTIONS

1. Remove loose surface dirt with water and a brush
2. Dilute 1:5 with water
3. Best to apply with a garden sprayer on a dry day
4. Thoroughly wet the surface of the stone
5. Keep treated surfaces protected from rain for at least 4 hours
6. All 24 to 48 hours for results to begin to show and for algae to die
7. Rinse with water after several days or simply wait for it to rain

LIMITATIONS

- For external use only
- Do not mix with other cleaners or allow product to come in contact with any non-recommended surfaces
- Contains Quaternary ammonium compounds, benzyl-C12-14 (even-numbered) Alkyldimethyl, chlorides

COVERAGE

Approximately 1 liter of ALGERASE diluted with 5 liters of water will cover approximately 387 square feet.

The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method and the severity of the problem.

HANDLING AND STORAGE

- Close container tightly after each use
- Store in original container only up to 12 months
- Store in temperatures between 40°F and 90°F
- Keep off of all other surfaces, clothing and plants
- Keep out of reach of children and animals

SPILLAGES

Spills of up to 1 liter may be washed into drains with water. Spills of over 1 liter should be absorbed with a suitable absorbent, e.g. sand or sawdust.

FIRST AID

INHALATION

Remove from exposure. If breathing becomes difficult seek medical attention.

EYE CONTACT

Hold eyelids apart and flush the eye continuously with running water for 15 minutes. If worn, remove contact lenses. If irritation persists, seek medical attention.

SKIN CONTACT

Remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

INGESTATION

Drink 1 or 2 glasses of water. Do NOT induce vomiting. If irritation or symptoms persist, seek medical attention.

SAFETY DIRECTIONS

Wear protective clothing including overall, gloves and eye protection to prevent skin and eye contact.

WARNING: CORROSIVE

- R34** Causes severe burns;
S1/2 Keep locked up and out of the reach of children;
S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice
S37/39 Wear suitable gloves and eye/face protection
S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)
R50 Very toxic to aquatic organisms

WARRANTY

EarthWorks™ warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST